

URB12200

Technical Datasheet



LITHIUM POWER

Li-Ion LFP Benefits Over SLA

- Uniform voltage during discharge
- No need to provide trickle charging to retain battery's charge
- Significantly lighter weight for the same amount of energy
- Battery does not become gaseous during use
- Nominal voltage is maintained over a wider temperature range

Features

- Integrated carry handles
- Can be properly charged using a 2 phase SLA charger
- IEC62133, 2nd edition compliant

Applications

- Scooters / wheelchairs
- UPS battery replacement
- Solar battery

Constant Voltage Charge at 23°C	Voltage Regulation	Initial Current	Maximum Current
Standby Use	13.6V	4A	20A
Cycle Use	14.4V	10A	20A

Technical Specifications

Part No	URB12200	
Chemistry	Lithium Iron Phosphate (LFP)	
IEC Designation	4IFR19/66-12	
Average Voltage	12.8V	
Nominal Capacity¹	21.6Ah	
Voltage Range	10.0V - 14.4V	
Max. Continuous Discharge	20.0A	
Max. Pulse Discharge²	120 ± 20A	
Energy¹	276Wh	
Energy Density	102Wh/kg, 121Wh/l	
Weight	Approx. 2.7 ± 0.2kg (6.28 ± 0.44lbs)	
Cycle Life³	>1500 cycles	
Operating Temperature	-20°C to 60°C discharging 0°C to 45°C charging	
Storage Temperature	0°C to 40°C	
Internal Resistance	≤60mΩ	
Self-Discharge @ 23°C	<5% per month	
Memory Effect	None	
Exterior/Housing	Hard plastic, ABS	
Terminals/Connector	M5 Screw Terminals	
Size	Length:	181 ± 2mm (7.12in)
	Width:	76 ± 2mm (3.00in)
	Height:	166 ± 3mm (6.53in)
Communications	None	
State of Charge Indicator	None	
Protection	Overcharge:	3.90V (per cell)
	Over Discharge:	2.00V (per cell)
	Over Current:	120 ± 20A (5-20ms)
	Over Temperature:	65 ± 5°C
	Short Circuit	
	Cell Imbalance	
Charging	Connect the battery to a DC power source using correct polarity and apply a maximum voltage of 14.4V. Limit the current to the recommended rate of 4.0A and hold 14.4V until the current declines to 400mA. Maximum charge rate is 20.0A. Alternatively, you may apply a maximum charge voltage of 13.6V (limiting the current to 4.0A) and hold indefinitely to maintain the battery in a continuous standby state-of-charge of between 70-90%.	
Safety	Material Safety Datasheet - MSDS00152 Refer also to Safety Guide UBM-5112	
Certification	CB Scheme ID:JPTUV-137471 UL 2054	
Transportation	Class 9 International and within U.S. ⁴ Excepted when shipped by motorcar or rail within U.S.	
Harmonized Tariff Schedule	8507.60.0000	

Notes

1. Using a C/5 discharge rate at 25°C.
2. Maximum pulse width of between 5ms and 20ms.
3. Number of consecutive C/5 rate discharges and recommended charges at 25±5°C until the battery reaches 80% of initial capacity.
4. Transportation regulations, classifications and lithium content are available on the Ultralife website

Dimensions

